

CX-350 CNC milling machine parameters:



1	Machine Body	Whole cover, iron cast bed structure, movable T-slot cast iron table		
2	System	Intelligent integration TK100 control system		
3	Spindle Motor	3.0KW water cooling spindle		
4	Three-axis motor	Japan YASKAWA 750Wservo motor and drivers		
5	Automatic lubrication system	pressurized volumetric automatic oiler, automatic balance		
6	Screw	original Taiwan TBI grinding ball screw		
7	Spindle cooling	water cooling		
8	Tool Holder	ER20		
9	Controller	Taiwan Delta inverter		
10	Three-axis roller guide	Taiwan HIWIN square rails		
11	The main electrical accessories	France Schneider contactor and leakage protector		
12	Work LED lamp	standard		
13	Three-axis telescopic shield	standard joint		
14	Full cover	standard dust cover		
15	Technical advantages	1. High-speed and stable large body		
Content		Unit	Parameters	Remarks
X/Y/Z-Axis Travel		mm	600*600*300	
Working Table Size		mm	600×600mm	
Table Max Load		kg	100kg-200kg	
Spindle Speed		r/pm	24000 rpm	
Spindle Motor Power		kw	3.0KW	
Spindle Taper Diameter		/	ER 20	
Positioning Accuracy		mm	±0.005mm/300mm	
Repeat Positioning Accuracy		mm	±0.003mm/300mm	
Electricity Demand		/	380V 3P 50HZ	
Accessories		1.Tool box (1 set)		